

I.T.S. Videoscopes XLED Pro Series

Ph: 949-232-5837

www.itsvideoscopes.com

iRIS XLED PRO Videoscope System



All In-One Compact Version Is Available



Technical data

iCAPTURE PRO

| | |
|--------------------------|--|
| Display size: | 7.0" |
| Display resolution: | 1024x600 Pixel |
| Operating system: | EIOS (Endoscopic Imaging Operating System) |
| interface: | USB |
| Power supply, primary: | Rechargeable Li-ion battery |
| Power supply, secondary: | 12V adapter (optional accessories) |
| Storage: | intern 16GB / USB (16GB in delivery) |
| Video format: | MPEG4 (.avi) |
| Image format: | BMP (.bmp), JPEG (.jpg), PNG (.png) |

OTHER DATA

| | |
|-------------------------------|--|
| Ergonomics: | rotatable + swiveling |
| Weight: | 1.28Kg |
| Dimensions: | see below |
| Housing: | Rugged PU with rubber shock protection |
| System operating temperature: | -25°C to +46°C |
| Storage temperature: | -25°C to +60°C |
| Relative humidity: | 95% less than - non condensing |

XLED PRO

| | |
|--------|---------------------------|
| Sensor | AIT Advanced Image Sensor |
|--------|---------------------------|

| PROBES (mm) | 2,4 | 3,0 | 4,0 | 6,0 |
|---------------------------|------------|------------|------------|------------|
| Working length (m) | 1,0 - 3,0 | 1,0 - 1,5 | 1,0 - 3,0 | 1,0 - 7,5 |
| Articulation | 2-way | 2-way | 4-way | 4-way |
| Integrated objective lens | • | • | • | • |
| Side view tip adapter | - | - | - | • |
| Side view option | • | • | • | • |

All In-One Compact Version Is Available
Please contact us for details, at 949-232-5837



I.T.S. Videoscopes
iTConcepts
Induction Technology Solutions Inc.
9133 Village 9,
Camarillo, CA 93012

Ph: 949-232-5837
www.itsvideoscopes.com

I.T.S. Videoscopes - Dedicated Customer Support
Tech. Center
iTConcepts
2921 E. Miraloma Ave. No. 14
Anaheim, CA 92806

Ph: 949-232-5837
www.itsvideoscopes.com